
This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED					
1		released for production.	11/17/2015	RJC	JAG					
2	16-0280	UPDATED TO NEW STANDARDS1 CH'D MATERIAL WAS 4140 Q&T/4142 Q&T IS 4140/4142; ADDED HEAT TREAT, ADDED FINISH SPEC3 CH'D DIM WAS Ø1.101+.000/003 S.F1 IS Ø1.099/1.096 (S.F1); ADDED NOTE "SPLIT LINEA"; CH'D NOTEA WAS EDM SOCKET IN HALF WITH MINIMAL MATERIAL LOSS. IS EDM SOCKET IN HALF WITH MINIMAL MATERIAL LOSS. IS EDM SOCKET MUST ALIGN; ADDED FINISH SPEC.	12/29/2016	SM	JAG					





- NOTES: 1. REFERENCE AGUSTA T/N AAB0026.
- 2. UPDATED RBWAAB0006.

DWG NO.

"M/R & T/R SERVO TORQUE SOCKET


RBWAAB0026 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/18 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125 / 1. BREAK ALL SHARP EDGES SPEC 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY DRAWN BY: CLOUGH


F										CHECKE	DU DU	ERFEL	.DT	AFTER PLA	AFTER PLATING 3. INTERPRET DIM AND TOL PER	
	ASSY QTY	ASSY QTY	B/O	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	OPPS AP	PR: AN	DERS	ON	ASME Y14.		
	α	QIII			Q					QA APPR	: LIN	IDSAY			USED ON MODEL	
				-1	1	CLAMP	4140/4142		2	APPROV	ED: GIL	GILBERT			AW139	
				-3	1	SOCKET	4140/4142		3	SCALE	1:1		DATE 1	1/1/2015	SHEET 1 OF 3	


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		
2	16-0280	-1 CH'D MATERIAL WAS 4140 Q&T/4142 Q&T IS 4140/4142; ADDED HEAT TREAT, ADDED FINISH SPEC.	12/29/2016	SM	JAG		











1:2

M/R & T/R SERVO TORQUE SOCKET

DWG NO. RBWAAB0026-1 MAT'L 4140/4142 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ±.5°

.X ± .1 SURFACES = 125/ HEAT RC 28-34
TREAT BLACK OXIDE SPEC QMSI-6.2.2, B.O. REV D 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: CLOUGH CHECKED: DUERFELDT OPPS APPR: ANDERSON QA APPR: LINDSAY USED ON MODEL APPROVED: GILBERT AW139 DATE 11/17/2015 SCALE

SHEET 2 OF 3


CLAMP

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	revisions									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED					
2	16-0280	-3 CH'D DIM WAS Ø1.101+.000/003 S.F1 IS Ø1.099/1.096 (S.F1); ADDED NOTE "SPLIT LINE∆"; CH'D NOTE∆ WAS EDM SOCKET IN HALF WITH MINIMAL MATERIAL LOSS. IS EDM SOCKET IN HALF WITH MINIMAL MATERIAL LOSS. FLATS ON SOCKET MUST ALIGN; ADDED FINISH SPEC.	12/29/2016	SM	JAG					

SCALE

1:2





SOCKET

M/R & T/R SERVO TORQUE SOCKET

DWG NO.	RBWAAB0026-3					
MAT'L 4140/4	1142	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES				
HEAT RC 38	-43	.XXX ± .005 FRACTIONS ± 1/8				
	K OXIDE	.XX				
SPEC QMSI-	6.2.2, B.O. REV D	1. BREAK ALL SHARP EDGES				
DRAWN BY:	CLOUGH	.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY				
CHECKED:	DUERFELDT	AFTER PLATING				
OPPS APPR:	ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009				
QA APPR:	LINDSAY	USED ON MODEL				
APPROVED:	GILBERT	AW139				

DATE 11/17/2015

SHEET 3 OF 3